

6 LANGUAGES VOICE (EN / FR / PL / ES / TR / CN)

32 00000000

00000000 000000 000000) 000000 000000

0000 000 /000000

35.5 :00000000 0000 000000 .1C-42.9C

2. 0 :00000000 000000C-118C

3. 000000 000000000 000

4. C / F 000000000 00000000

00000000 00000000 00 0000000000 00000000 .5

000000 000000000 0000000000 .6

0000000000 00000000 000000 .7

0 :0000000000 0000000000 .8C-3.0C

9. 000 000000 000000

00 00000000 00000000: EN 12470-5 0 ASTM 1965-98

5 :00000000 00000000CM-8CM

:000000000 0000 000

(°F 107.6-95.9) °C 42.9-35.5 °F 0.5 / °C 0.3 ±

:00000000 000

(°F 95.7-89.6) °C 35.4-32.0 °F 0.5 / °C 0.3 ±

000000000 0000 0.1 / 000000 0000 0.1 :00000000

10.0 :00000000 0000 ° C-40.0 ° C (50.0 ° F-104.0 ° F)

000000 000 0 80≥ 00000000

25.0- :00000000 0000 ° C-55.0 ° C (-13.0 ° F-131.0 ° F)

000000 000 0 90 ≥ 00000000

00000000 * 2 :000000000 AA





查詢詳情 請電: thermometersupplier.com

查詢詳情 請電: sanieleung@dor-medex.com