□□□□□□□ □□□□□□□□

□□□□□□□□ □□□□□□□□ :□□□□□□□ □□□ JT002NM
.41 1 □□ □□□□□□□□ □ □□□□□□□□ 1.5 :□□□□□□□ □□□□□□□□
□□□□□□□□ 0.1 :□□□□□□□ □□□□□□□□
(□□□□□□ □□ □□□□□□ 10 □□□□□ □□□□□□□ □□□□□ □□□) □□□□□□□ 1100 □□□□□□ :□□□□□□□□□ □□□
□□□□□□□□□ :□□□□□□□□□□ □□□□□
□□□□□□□ □□□□□□□ :□□□□□□□ □□□□□□
□□□□□□ 3 :□□□□□□□□ □□□□□ □□□ □ + °c (°f) □□□□□□□□□ □□□□□ 0.1 □□
43- □° 32) □□□□□□ □□□□□ 0.1 ± :□□□□□□□ □□□ °c)
± 0.18 °f (89-60 °f-109.40 °f)
□ 2 :□□□□□□□ □□□
89.6) □□□□□□ □□□□□ 43 □□□ □□□□□□ □□□□□ 32 :□□□□□□□ □□□□□ °f 109.40 □□□ °f)
50) □□□□□□ □□□□□ 40 + □□□ □□□□□□ □□□□□ 10 + :□□□□□□□□ □□□□□□□□ □□□□□ :□□□□□□□□□□ □□□□□ °f 104 □□□ °f)
4-) □□□□□□ □□□□□ 60 + □□□ □□□□□□ □□□□□ 20-:□□□□□□□□ □□□□□ °f 140 □□□ °f)
95-30 □□□□□□□□ □□□□□□□□ :□□□□□□□□□ □□□□□□□□ □□□□□% RH
(□□□□□□□□ □□□□□□□□□) □□□□□ 15 □□□□□□ :□□□□□□
20 :□□□□□□□□mm (W) * 130 (□) □□ 13 * (□) □□
□□□□□□□□□ □□ □□□□□□□□□□□□ □□□□□□□□) □□□□□□□□□ □□□□□□□ :□□□□□□□□□□ LR4) □ □□□□□ □ □□□□□□□□ □□□□□
.□□□□□□□□□
□□□□□□□/□□□□□□□□ □□□□□ 80 :□□□□□□□□□
30 * □□ 33 :□□□□□□□ □□□□□□□ □□□mm * 260 □□

show details

01 battery cover

This product USES the button battery, push the battery cover and replace the battery

02 Internal Battery

Open the battery cover to see the internal details determine the quality

03 Elliptic switch

A button switch, convenient and concise

04 LED display screen

The LED screen shows the digital value is more intuitive

05 Heat detector

Using soft head probe, safe and convenient



□□□□□□□ □□□□ □□□□□□□:

A variety of test temperature methods
Oral Thermometry
Oral Thermometry
axillary measurement
Anal measurement method