

Accuracy: $\pm 0.05^{\circ}\text{C}$ (32°C - 43°C)
 $\pm 0.1^{\circ}\text{F}$ (89.60°F - 109.40°F)

Quantity: 2 pieces

Operating range: 43°C (89.6°F) to 109.40°C (32°C)

Storage range: 40°C (104°F) to 50°C ($+10^{\circ}\text{C}$)

Storage range: -20°C (-4°F) to 140°F

Temp range: 30-95% humidity

Weight: 15g (0.53oz)

Dimensions: 20mm(W)*130mm(L)*13mm(d)

Material: ABS (UL94V-0), LR4 battery, stainless steel

Quantity: CTN 80pcs /

CTN size: 331mm * 305mm * 260mm

Instructions:

1. Turn on the device by pressing the power button. The LCD screen will display "Lo".

2. Hold the device in your hand and breathe into the sensor.

* Note: LCD displays "Lo" when the temperature is 32°C (90°F) or lower. The LCD displays "Hi" when the temperature is 42.9°C (109.9°F) or higher.



Step2. Turn on the device (power) and display the screen

) Turn on the device: "v" The device will display "Lo" when the temperature is 32°C (90°F) or lower. The device will display "Hi" when the temperature is 42.9°C (109.9°F) or higher. The device will display the current temperature when the sensor is placed on the forehead.

Step3

Hold the device in your hand and breathe into the sensor. The device will display the current temperature. The device will display "Lo" when the temperature is 32°C (90°F) or lower. The device will display "Hi" when the temperature is 42.9°C (109.9°F) or higher. The device will display the current temperature when the sensor is placed on the forehead.

Step4.

00000 0000 00 00000 0000 0000 00 000, 0000000 00000 0000 00 000 0000 000 0000 00 000
0000 000 000000 000 0000000000 0000 00, 00 0000 000000000 0000 00 **around10** 0000 00 000
000 00 00000
0000000000 0000 000000000000 00000 000 0000000000